

# SILVER SD SERIES WHITE LIGHT ILLUMINATOR

## S-S09D-W

- High power white light illuminator provides high power illumination for CCTV cameras. Delicate housing and strong materials for great heat dissipation ability and zero maintenance
- 30,000 hours lifetime of LED.
- 3 years warranty.



## Professional Design

- Two stages of constant current circuit avoid LED away from instantly impulse impact when started.
- Low failure rate of products is guaranteed by the professional in-house optimized independent circuit technology, which has been widely used in our LED illuminators for more than 5 years.
- Wide edge of silica gel circle and water stop line ensure IP66 waterproof and dustproof level.
- Twice direct cooling heat sink processing enable to increase the cooling coefficient and prolong the service life of the product.
- Patent design hexagonal spherical light sensor more accurately responses ambient brightness and improves accuracy of automatic light control.
- Flexible angle adjustable bracket can extend the illuminance range widely.
- Robust cooling fin design is available the illuminator working at -40°C to 50°C.
- Super energy saving circuit with low electrical power consumption.

## Qualified Material

- Super power dot-matrix LED with strong light effect, long service life and low light decline feature.
- High efficient twice optical lens processing achieves 90% of the luminous efficiency.
- The housing adopts high thermal conductivity aluminum to enhance heat dispersion property.
- Stainless steel bracket and screw ensure low maintenance.

## Wide Range of Application

- Recommended for security at ports, railway systems, border, prisons, traffic LPR/ANPR, ITS as well as large public places lighting.

## Basic Function

- To improve performance of the weak light camera, thereby enhancing the picture effects at night.
- Conventional night monitoring
- The function of video analysis at night
- Reduce signal noise and other image distortion
- Reduce the network bandwidth requirements
- Energy saving by power factor correction
- Reduce the equipment cost
- Lower cost of installing and wiring

## Viewing picture at night



With white light

Without white light

# SILVER SD SERIES WHITE LIGHT ILLUMINATOR

## Picture




## Product certificate



## Technical Specification

LED type	9pcs high power white light LED
Color temperature	3000-3500K/5500-6000K
Luminous Flux	1800lm
Voltage	AC85-265V/DC12V/AC24V
Power consumption	20W
Day and night switch	Auto (build in photocell)
Mounting	Wall mounting "U" bracket
Temperature	-40°C to 50°C
Grade of protection	IP66
Color	Beige
Housing	Aluminium
Panel	High light transmittance toughened glass
N.W	1.25KG
G.W	1.55KG
Dimension	135*110*91mm
Packing dimension	190*180*135mm

## Drawing



## Model for selection

Model	Beam angle	Viewing distance
S-S09D-15-W	15°	140m
S-S09D-30-W	30°	110m
S-S09D-45-W	45°	80m
S-S09D-60-W	60°	60m
S-S09D-90-W	90°	45m
S-S09D-120-W	120°	25m

\*Viewing distance is tested by Sony 1/3 CCD Camera with 0.01LUX. .

To achieve the distance needed, please pay attention to your camera specification and lens before purchase. It is normal phenomenon that distance may vary due to different cameras and lens.